

UniFusionTM

The Science of Laminated Floor Matting

What is UniFusion?

UniFusion is a revolutionary bonding process that uses heat and pressure to fuse a floor matting top surface to a base material. The resulting finished product is virtually a single piece, eliminating any possibility of de-lamination. In fact, we're so confident in the UniFusion bond that we guarantee it...for life! (see warranty for details)

Why UniFusion?

UniFusion allows us to create an unbreakable bond resulting in far superior product quality, and eliminates the possibility of de-lamination, a problem inherent in laminated floor matting. De-lamination occurs when a mat top surface separates from the base material. This can cause the top to buckle, or the edges to curl, creating a trip hazard. By eliminating de-lamination, the end result is a safer work environment, and reduced costs associated with injury claims.

The Facts*:

- Slips, trips, and falls are the 2nd leading cause of workplace injuries
- Injuries due to falls result in an average 12 days away from work
- The average cost for a workman's compensation claim due to a slip, trip, and fall accident is \$46,592

*National Safety Council Injury Facts®, Top Work-Related Injuries 2016-2018 data

Warranty:

We are so confident in the UniFusion process that we offer the following UniFusion lifetime warranty:

NoTrax guarantees the bond on all NoTrax laminated floor matting products that incorporate the UniFusion lamination process, for the lifetime of the mat. The bond on these products is guaranteed under normal conditions of use in reasonable dry application environments, or a full refund or replacement mat (based on manufacturer's discretion) will be issued. Proof of purchase is required for all refunds or replacements. This lifetime warranty protects against de-lamination or bond failure, and does not cover issues unrelated to the bond such as wear or foam tears. All NoTrax laminate top products with foam backing are covered by the standard warranty against manufacturer's defects and are not guaranteed against spike heels or stool legs. Laminated matting products that are non-standard widths or require blunt cut edges may not use the UniFusion process.



Laminated floor matting has two materials fused together, a top surface and base material. UniFusion is a unique bonding process that permanently bonds the materials together for a safer, longer-lasting finished product.







Available on these NoTrax products:

485	Ergo Trax™	980	Pebble Trax® Grande™
985	Ergo Trax™ Grande™	482	Bubble Trax®
479	Cushion Trax®	782	Bubble Trax® Ultra™
975	Cushion Trax® Ultra™	982	Bubble Trax® Grande™
979	Saddle Trax®	474	Ergo Mat [™]
490	Dura Trax®	974	Ergo Mat™ Grande™
976	Dura Trax® Ultra™	470	Marble Sof-Tyle™
990	Dura Trax® Grande™	970	Marble Sof-Tyle™ Grande™
477	Woodgrain Sof-Tyle [™]	826	Diamond Stat™
977	Woodgrain Sof-Tyle Grande™	927	Diamond Stat™ Grande™
480	Pebble Trax®	926	Smooth Stat™

NoTrax

5655 West 73rd Street Chicago, IL 60638 **Email:** customerservice@notrax.com

NoTrax.com