



Interlocking Rubber Mat Niru® Cushion-Ease® GSII™ 856S

Product Images





Short Description

- Resilient rubber compound and unique multi-nib support design offers exceptional fatigue relief
- Solid top design with an anti-slip surface texture is easy to clean
- Easy to snap-together system for on-site custom work station platforms
- Nitrile provides highest level of resistance to chemicals, oils and greases
- GSII™ offers the ultimate in durability, performance and traction in harsh environments
- Compatible with any Cushion-Ease® family mats
- 551 M.D. Ramp System® and 552 extra wide M.D.-X Ramp System™ available

Description

Niru® Cushion-Ease® GSII™ Solid is a high performance interlocking anti-fatigue matting system made with a resilient rubber compound with a solid top anti-slip surface texture and a multi-nib backing for comfort and


ergonomic support of the mat. Made of 100% nitrile rubber compound that provides the highest resistance to chemicals, cutting fluids, animal fats, oils and greases. GSII™ has a silicon carbide grit surface for extreme traction in the harshest of work environments. Niru® Cushion-Ease® GSII™ Solid mold has been engineered to produce a mat that is functional, comfortable and durable. All Cushion-Ease® series mats have a male/female interlocking system for individual workstations, long runs, unique configurations and wall-to-wall floors. Also compatible with NoTrax® M.D. Ramp System® for easy on-site custom configurations and trip-resistant platforms.

Specifications

| | |
|-------------------------|--|
| Model No | 856S0033BL |
| Color | Black |
| Dimensions | 3ft x 3ft |
| Thickness | 3/4in |
| UPC | 662641769151 |
| Available Colors | Black |
| Overall Thickness | 3/4 |
| Standard sizes | 3'x3' |
| Group | Ergonomic, Anti-fatigue & Safety Matting |
| Environment | Wet/Dry and Oily Areas |
| Special Characteristics | Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals |
| Recommended Use | For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms |
| Special Remarks | GSII™ excels in the harshest industrial environments because it resists the chemicals, oils, and greases that cause traditional rubber matting to breakdown. |
| Surface | Grip Step II® |
| Edges | Attachable beveled edges are available |
| Usage Intensity | Heavy duty |
| Custom Description | Available #551 M.D. Ramp System® or #552 M.D.-X Ramp System™ attachable ramps |
| Installation | Interlocking mats allow on-site customization. Square snap-together units can be assembled effortlessly. |
| Material Specifications | 100% Nitrile rubber |
| Process | Compression Molding |
| Pallet Quantity | 36 |
| Weight Lbs/sqft | 3.2 |

| | |
|------------------------|---|
| Thickness Inch | 3/4in |
| Fire Rating US | Pass |
| REACH Compliant | Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals). |
| Anti-Fatigue Rating | Best |
| Slip Resistance Rating | Superior |
| Wear Resistance Rating | Superior |

Prop 65

 **WARNING:** This product can expose you to chemicals including diisodecyl phthalate which is known to the State of California to cause birth defects or reproductive harm, and beryllium which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov. For more information, visit www.P65Warnings.ca.gov.